

TECHNICAL SHEET

1649-30 FATTY

Mounting: Wall Sconces

Environment: Indoor - Dry location

Materials: Metal

Voltage: 120-277V 50/60Hz

Source: LED 13,5W - 3000K - CRI=90

Lumen: white 377lm - bronze 251lm

Lighting control: Dimmable 0-10V / Dimmable phase cut (120V only)

Certification:



1649-31 TALL

Mounting: Wall Sconces

Environment: Indoor - Dry location

Materials: Metal

Voltage: 120-277V 50/60Hz

Source: LED 13,5W - 3000K - CRI=90

Lumen: white 377lm - bronze 251lm


Lighting control: Dimmable 0-10V / Dimmable phase cut (120V only)

Certification:



1649-30

1649-31



L9,8" x W3,2" x H15,7"



L6,2" x W3,1" x H23,6"

Finishes

Structure



Brushed bronze



Matt white

NOTE

2700K version available after technical verification

CODES	SIZE	STRUCTURE	SHADE	DETAILS
1649-31-1700-DXNV	tall wall sconces	brushed bronze		dimnable 0-10V / dimnable phase cut
1649-31-0100-DXNV	tall wall sconces	matt white		dimnable 0-10V / dimnable phase cut
1649-30-1700-DXNU	fatty wall sconces	brushed bronze		dimnable 0-10V / dimnable phase cut
1649-30-0100-DXNU	fatty wall sconces	matt white		dimnable 0-10V / dimnable phase cut