

# T46LED 20 DIMMERABLE \_HIGH EFFICIENCY



Code	21641
Lighting technology used:	LED
Non-directional or directional (NDLS / DLS):	NDLS
Light source cap-type (or other electric interface):	E27
Mains or non-mains (MLS / NMLS):	MLS
Dimmable:	yes
On-mode power (Pon), expressed in W	20 (W)
Energy consumption (kWh/1000 h)	20 (kWh/1000h)
Energy efficiency class	E
Useful luminous flux (Φuse)	2300 in sphere (360°)
Correlated colour temperature K	2700

Height	140 (mm)
Width	46 (mm)
Depth	46 (mm)
Claim of equivalent powerc	yes / -
If yes, equivalent power (W)	141 (W)
Chromaticity coordinates (x and y)	
	X 0,44
	Y 0,403
Peak luminous intensity (cd)	not relevant (cd)
Beam angle in degrees, or the range of beam angles that can be set	not relevant (°)
R9 colour rendering index value	2
Survival factor	0,9
Lumen maintenance factor	0,96
displacement factor (cos φ1)	0,7
Colour consistency in McAdam ellipses	5
Flicker metric (Pst LM)	1
Stroboscopic effect metric (SVM)	0,4



MARINO CRISTAL SPA  
Via Guardia del Consiglio, 29/31  
47899 - Serravalle  
REPUBBLICA DI SAN MARINO

TEL +378 0549 901188  
FAX +378 0549 900612  
www.marinocrystal.com  
marinocrystal@marinocrystal.com

