



**gic** Design: Klaus Nolting



**gic** Design: Klaus Nolting

**Lichttechnik:**  
230V Power LED  
2700K  
L70/50.000 h

dimmbar

**Installation:**  
2x Kabeleinführung;  
Anschlussklemme  
3x 1,5 mm<sup>2</sup>

**Material:**  
Aluminiumguss  
pulverbeschichtet  
Glas satiniert

**Schutzart:**  
IP65



**Lichtrichtung:**



light technology:  
230V Power LED  
2700K  
L70/50.000 h

dimmable

installation:  
2x cable entry point;  
connection terminal  
3x 1,5 mm<sup>2</sup>

material:  
aluminium die-casting  
powder-coated  
glass satined


protection class:  
IP65



light direction:




**gic base**



Farbe colour	Art.-Nr. item no.	Systemleistung system performance
anthracite RAL 7016	93250-AN	8 W/360 lm
pure white RAL 9016	93250-WH	8 W/360 lm
deep black RAL 9005	93250-BL	8 W/360 lm

**Erforderliches Zubehör** required accessory

**gic cover**



Farbe colour	Art.-Nr. item no.	Material material
anthracite RAL 7016	93250-C-AN	Edelstahl pulverbeschichtet stainless steel powder-coated
pure white RAL 9016	93250-C-WH	Edelstahl pulverbeschichtet stainless steel powder-coated
deep black RAL 9005	93250-C-BL	Edelstahl pulverbeschichtet stainless steel powder-coated
brass polished	93250-CB-PO	Messing poliert brass polished
brass brushed	93250-CB-BR	Messing gebürstet brass brushed
stainless steel polished	93250-CS-PO	Edelstahl poliert stainless steel polished
stainless steel brushed	93250-CS-BR	Edelstahl gebürstet stainless steel brushed

Größe in mm  
size in mm